

Blizzard INT e90-297 RZ

GLOSS SILVER/BLACK/GREEN



E-BIKE

E-BIKE SYSTÉM	SHIMANO STEPS EP8 - Middle Drive Unit
MOTOR	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATÉRIA	DARFON, 630 Wh, in-frame mount
DISPLEJ	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart plus charger, charging time up to 5,5 hours
MAX SUPPORT SPEED	25 km/h
NABÍJACIE CYKLY	1000/60% of original capacity
DISTANCE RANGE	150 km (ECO mode) w/EP8 range 20% up

FRAMESET

COLOUR	Gloss Silver/Black/DVO Green
RÁM	Alloy Al-6061 T6 Custom tubing, RME01 630Wh, Floating Pivot Suspension, 130-140 mm travel, Trail Advanced Geometry, Shark Spine EVO 29er&27.5+, 2nd Gen. Battery Integration, BOOST 148x12, Disc Brake Post Mount, Inner Cable Routing, Adjust. seatpost ready
HLAVOVÉ SLOŽENIE	ACROS AZX-251, Zero Stack, 1-1/8"x1.5", BlockLock
VIDLICA	DVO Diamond E2, LSC, Internal OTT Adjust, Rebound, Tapered, 15x110mm axle, 160mm travel
ZADNÍ ODPRUŽENÍ	DVO Jade X Coil, external rebound, 2 position compression (High/Low), LS Spring: 500lbs, 550lbs, 600lbs, size 210x55mm
VELKOSŤ	17.0"(M), 19.0"(L), 21.0"(XL)

DRIVETRAIN

POČET RÝCHLOSTÍ	1x11, 36 x 11-50, 455 %
RADENIE	SHIMANO XT SL-M8130-IR11, 11-speed
ZADNÝ MENIČ	SHIMANO XT RD-M8130 Shadow Plus
KLUKY S PREVODNÍKMI	SHIMANO XT FC-M8150, 36T
CASSETTE	SHIMANO CS-LG600-11, 11-50T
REŤAZ	SHIMANO CN-LG500
PEDÁLY	Pedals not included

COMPONENTS

RIADÍTKA	Race Face Turbine R 35, 20mm rise, 800mm, 35mm
PREDSTAVEC	Race Face Turbine R Alloy, 35xE40mm, 0°
MADLÁ	ONE1 VL-G1661D2N, Lock-On
BRZDY (P/Z)	SHIMANO XT BL-M8100/BR-M8120, 203/203 rotor, hydraulic disc brake
SEDLOVKA	ONE1 Alloy, MT171, dropper post 150&170mm travel, 30.9x440mm&480mm

WHEELS

PREDNÝ NÁBOJ	SHIMANO XT HB-M8010-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
ZADNÝ NÁBOJ	SHIMANO XT FH-M8010-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RÁFIKY	WTB HTZ TRAIL i30, 29" & 27.5", 32H
PLÁŠTE	WTB Vigilante TCS Tough/High Grip, Tritec, 29x2.50", WTB Trail Boss TCS Tough/Fast Rolling, Tritec, 27.5x2.60" E-Ready
ŠPICE	Sapim Leader, Stainless Black

WEIGHT

23.5 Kg (M size)

FRAME SIZE	17.0" (M)	19.0" (L)	21.0" (XL)
RIDER SIZE (cm)	165 - 185	175 - 195	185 - 200
WHEEL SIZE	29 & 27.5"	29 & 27.5"	29 & 27.5"
CHAINSTAY LENGTH (MM)	449	449	449
EFFECTIVE TOP TUBE LENGTH (MM)	605	630	650
REACH (MM)	426	451	471
STACK HEIGHT (MM)	623	623	623
BB DROP (MM)	0	0	0
WHEELBASE (MM)	1 209	1 234	1 254
HEAD TUBE ANGLE (DEGREE)	64	64	64
SEAT TUBE ANGLE (DEGREE)	74	74	74
HEAD TUBE LENGTH (MM)	120	120	120
SEAT TUBE LENGTH (MM)	415	460	500
SEAT POST LENGTH TRAVEL (mm)	440 / 150	480 / 170	480 / 170
HANDLEBAR WIDTH / RISE (mm)	800 / R20	800 / R20	800 / R20
STEM LENGTH (MM)	40	40	40
CRANK LENGTH (MM)	165	165	165

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.